

BBBBBBBBBBBB		AAAAAAA		SSSSSSSSSS		RRRRRRRRRR		TTTTTTTTTT		LLL
BBBBBBBBBBBB		AAAAAAA		SSSSSSSSSS		RRRRRRRRRR		TTTTTTTTTT		LLL
BBBBBBBBBBBB		AAAAAAA		SSSSSSSSSS		RRRRRRRRRR		TTTTTTTTTT		LLL
BBB	BBB	AAA	AAA	SSS		RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA	SSS		RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA	SSS		RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA	SSS		RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA	SSS		RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA	SSS		RRR	RRR	TTT		LLL
BBBBBBBBBBBB		AAA	AAA	SSSSSSSS		RRRRRRRRRR		TTT		LLL
BBBBBBBBBBBB		AAA	AAA	SSSSSSSS		RRRRRRRRRR		TTT		LLL
BBBBBBBBBBBB		AAA	AAA	SSSSSSSS		RRRRRRRRRR		TTT		LLL
BBB	BBB	AAAAAAAAAAAA			SSS	RRR	RRR	TTT		LLL
BBB	BBB	AAAAAAAAAAAA			SSS	RRR	RRR	TTT		LLL
BBB	BBB	AAAAAAAAAAAA			SSS	RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA		SSS	RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA		SSS	RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA		SSS	RRR	RRR	TTT		LLL
BBB	BBB	AAA	AAA		SSS	RRR	RRR	TTT		LLL
BBBBBBBBBBBB		AAA	AAA	SSSSSSSSSS		RRR	RRR	TTT		LLLLLLLLLLLL
BBBBBBBBBBBB		AAA	AAA	SSSSSSSSSS		RRR	RRR	TTT		LLLLLLLLLLLL
BBBBBBBBBBBB		AAA	AAA	SSSSSSSSSS		RRR	RRR	TTT		LLLLLLLLLLLL

BBBBBBBB	AAAAAA	SSSSSSSS	MM	MM	AAAAAA	TTTTTTTTTT	TTTTTTTTTT	RRRRRRRR	NN	NN
BBBBBBBB	AAAAAA	SSSSSSSS	MM	MM	AAAAAA	TTTTTTTTTT	TTTTTTTTTT	RRRRRRRR	NN	NN
BB	AA	SS	MMM	MMM	AA	TT	TT	RR	NN	NN
BB	AA	SS	MMM	MMM	AA	TT	TT	RR	NN	NN
BB	AA	SS	MM	MM	AA	TT	TT	RR	NNNN	NN
BB	AA	SS	MM	MM	AA	TT	TT	RR	NNNN	NN
BBBBBBBB	AA	SSSSSS	MM	MM	AA	TT	TT	RRRRRRRR	NN	NN
BBBBBBBB	AA	SSSSSS	MM	MM	AA	TT	TT	RRRRRRRR	NN	NN
BB	AAAAAAAAA	SS	MM	MM	AAAAAAAAA	TT	TT	RR	NN	NNNN
BB	AAAAAAAAA	SS	MM	MM	AAAAAAAAA	TT	TT	RR	NN	NNNN
BB	AA	SS	MM	MM	AA	TT	TT	RR	NN	NN
BB	AA	SS	MM	MM	AA	TT	TT	RR	NN	NN
BBBBBBBB	AA	SSSSSSSS	MM	MM	AA	TT	TT	RR	NN	NN
BBBBBBBB	AA	SSSSSSSS	MM	MM	AA	TT	TT	RR	NN	NN
									
									
									
									

LL	IIIIII	SSSSSSSS
LL	IIIIII	SSSSSSSS
LL	II	SS
LL	II	SS
LL	II	SS
LL	II	SS
LL	II	SSSSSS
LL	II	SSSSSS
LL	II	SS
LL	II	SS
LL	II	SS
LL	II	SS
LLLLLLLLLL	IIIIII	SSSSSSSS
LLLLLLLLLL	IIIIII	SSSSSSSS

(2) 63
(4) 285

DECLARATIONS
BASSMAT_TRN - Transpose one matrix into another


```
0000 1 .TITLE BASSMAT_TRN
0000 2 .IDENT /1-013/
0000 3
0000 4
0000 5 *****
0000 6 *
0000 7 * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 8 * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 9 * ALL RIGHTS RESERVED.
0000 10 *
0000 11 * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 12 * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 13 * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 14 * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 15 * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 16 * TRANSFERRED.
0000 17 *
0000 18 * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 19 * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 20 * CORPORATION.
0000 21 *
0000 22 * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 23 * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 24 *
0000 25 *
0000 26 *****
0000 27
0000 28
0000 29 ++
0000 30 FACILITY: BASIC code support
0000 31
0000 32 ABSTRACT:
0000 33
0000 34 This module writes the transpose of a matrix into a second matrix.
0000 35
0000 36 ENVIRONMENT: User Mode, AST Reentrant
0000 37
0000 38 --
0000 39 AUTHOR: R. Will, CREATION DATE: 10-Jul-79
0000 40
0000 41 MODIFIED BY:
0000 42 ++
0000 43 1-001 - Original
0000 44 1-002 - Fix test for 'same array' for virtual. RW 15-Feb-1980
0000 45 1-003 - Add support for byte, g & h floating. PLL 22-Sep-81
0000 46 1-004 - More modifications for new data types. PLL 24-Sep-81
0000 47 1-005 - Change shared external references to G^ RNH 25-Sep-81
0000 48 1-006 - Substitute a macro for the calls to the array fetch and store
0000 49 routines. This should speed things up. PLL 9-Nov-81
0000 50 1-007 - STORE macro must handle g & h floating. PLL 11-Nov-81
0000 51 1-008 - Correct a run-time expression in the FETCH and STORE macros.
0000 52 PLL 20-Jan-82
0000 53 1-009 - Don't list macro expansions. PLL 16-Mar-82
0000 54 1-010 - Remove FETCH and STORE macros; they are now located in macro
0000 55 library MATRIXMAC.OLB. Also added support for arrays of
0000 56 descriptors. LB 19-May-82
0000 57 1-011 - Change own storage to stack storage. LB 9-Jul-1982
```

BASSMAT_TRN
1-013

K 14

15-SEP-1984 23:55:09 VAX/VMS Macro V04-00
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1

Page 2
(1)

```
0000 58 ; 1-012 - Allow gfloat results to be stored in a double destination, and
0000 59 ;               vice versa. PLL 7-Oct-1982
0000 60 ; 1-013 - Use G^ for ALL externals. SBL 16-Nov-1982
0000 61 ;--
```

DECLARATIONS

```
0000 63      .SBTTL  DECLARATIONS
0000 64      :
0000 65      : INCLUDE FILES:
0000 66      :
0000 67      :
0000 68      $DSCDEF      ; define descriptor offsets
0000 69      $SFDEF      ; use to get scale
0000 70      :
0000 71      :
0000 72      : EXTERNAL DECLARATIONS:
0000 73      :
0000 74      :
0000 75      .DSABL  GBL      ; Prevent undeclared
0000 76      :              ; symbols from being
0000 77      :              ; automatically global.
0000 78      .EXTRN  BASSK_ARGDONMAT      ; signalled if all 3 blocks
0000 79      :              ; not present in array desc
0000 80      :              ; or dimct = 0
0000 81      .EXTRN  BASSK_DATTYPERR      ; signalled if dtype of array
0000 82      :              ; isn't word long float double
0000 83      .EXTRN  BASSK_MATDIMERR      ; signalled if src matrix has
0000 84      :              ; only 1 dimension
0000 85      .EXTRN  BASSK_ILLOPE      ; signalled if DSC$A_POINTER is
0000 86      :              ; same in src and dest matrices
0000 87      .EXTRN  BASS$TO_FA_B_R8      ; array element store for byte
0000 88      .EXTRN  BASS$TO_FA_W_R8      ; array element store for word
0000 89      .EXTRN  BASS$TO_FA_L_R8      ; array element store for long
0000 90      .EXTRN  BASS$TO_FA_F_R8      ; array element store - float
0000 91      .EXTRN  BASS$TO_FA_D_R8      ; array element store - double
0000 92      .EXTRN  BASS$TO_FA_G_R8      ; array element store - gfloat
0000 93      .EXTRN  BASS$TO_FA_H_R8      ; array element store - hfloat
0000 94      .EXTRN  BASS$FET_FA_B_R8      ; array element fetch - byte
0000 95      .EXTRN  BASS$FET_FA_W_R8      ; array element fetch - word
0000 96      .EXTRN  BASS$FET_FA_L_R8      ; array element fetch - long
0000 97      .EXTRN  BASS$FET_FA_F_R8      ; array element fetch - float
0000 98      .EXTRN  BASS$FET_FA_D_R8      ; array element fetch - double
0000 99      .EXTRN  BASS$FET_FA_G_R8      ; array element fetch - gfloat
0000 100     .EXTRN  BASS$FET_FA_H_R8      ; array element fetch - hfloat
0000 101     .EXTRN  BASSMAT_REDIM      ; check if redimensioning of
0000 102     :              ; dest array is necessary, if
0000 103     :              ; so, do it
0000 104     .EXTRN  BASS$SCALE_R1      ; scale the double precision
0000 105     .EXTRN  MTH$DINT_R4      ; truncate dbl precision number
0000 106     .EXTRN  BASS$STOP      ; signal fatal errors
0000 107     .EXTRN  BASS$FETCH_BFA
0000 108     .EXTRN  BASS$STORE_BFA
0000 109     :
0000 110     :
0000 111     : MACROS:
0000 112     :
0000 113     :
0000 114     : SBASSMAT_TRN      transpose loop algorithm, see next page
0000 115     : FETCH      fetch an element from an array (found in macro
0000 116     :              ; library MATRIXMAC.OLB)
0000 117     : STORE      store an element into an array (found in macro
0000 118     :              ; library MATRIXMAC.OLB)
0000 119     :
```


DECLARATIONS

```

0000 120 :
0000 121 : EQUATED SYMBOLS:
0000 122 :
0000 123 :
00000004 0000 124 first_arg = 4 ; arg offset for str copy
00000008 0000 125 second_arg = 8 ; arg offset for str copy
0000000C 0000 126 index1 = 12 ; stack offset for str copy
00000010 0000 127 index2 = 16 ; stack offset for str copy
00000014 0000 128 temp_desc = 20 ; stack offset for str copy
00000000 0000 129 lower_bnd2 = 0 ; stack offset for temp
00000004 0000 130 lower_bnd1 = 4 ; stack offset for temp
00000008 0000 131 upper_bnd1 = 8 ; stack offset for temp
0000000C 0000 132 value_desc = 12 ; output descriptor
0000000C 0000 133 str_len = 12 ; length field in desc
0000000E 0000 134 dtype = 14 ; data type field in desc
0000000F 0000 135 class = 15 ; class field within desc
00000010 0000 136 pointer = 16 ; pointer to data
00000014 0000 137 data = 20 ; data
00000018 0000 138 dsc$l_l1_1 = 24 ; desc offset if 1 sub
0000001C 0000 139 dsc$l_u1_1 = 28 ; desc offset if 1 sub
0000001C 0000 140 dsc$l_l1_2 = 28 ; desc offset if 2 sub
00000020 0000 141 dsc$l_u1_2 = 32 ; desc offset if 2 sub
00000024 0000 142 dsc$l_l2_2 = 36 ; desc offset if 2 sub
00000028 0000 143 dsc$l_u2_2 = 40 ; desc offset if 2 sub
0000 144 :
0000 145 :
0000 146 : OWN STORAGE:
0000 147 :
0000 148 :
0000 149 :
0000 150 :
0000 151 : PSECT DECLARATIONS:
0000 152 :
00000000 153 .PSECT _BASSCODE PIC, USR, CON, REL, LCL, SHR, -
0000 154 EXE, RD, NOWRT, LONG
0000 155

```

DECLARATIONS

```
0000 157 :+
0000 158 : This macro contains the looping mechanism for accessing all elements of
0000 159 : an array. It also contains all the logic for all the combinations of data
0000 160 : types and scaling. A macro is used to make it easy to maintain the parallel
0000 161 : code for all the different data types.
0000 162 :-
0000 163
0000 164 .MACRO $BASSMAT_TRN src_dtype, dest_dtype ; transpose algorithm
0000 165
0000 166 :+
0000 167 : Loop through all the rows. Row and column upper and lower bounds have been
0000 168 : initialized on the stack.
0000 169 :-
0000 170
0000 171 LOOP_1ST_SUB'src_dtype'dest_dtype':
0000 172     MOVL     lower_bnd2(SP), R11                ; R11 has 2nd lower bound
0000 173
0000 174 :+
0000 175 : Loop through all the elements (columns) of the current row. Column lower
0000 176 : bound is initialized in R11. Column upper bound is on the stack.
0000 177 : Distinguish array by data type so that the correct fetch routine can
0000 178 : retrieve the data, the correct conversion can be done and the correct
0000 179 : store routine can be called.
0000 180 :-
0000 181
0000 182 LOOP_2ND_SUB'src_dtype'dest_dtype':
0000 183
0000 184 :+
0000 185 : Get the data from source array
0000 186 :-
0000 187
0000 188     MOVL     R10, R0                ; pointer to array dest
0000 189     MOVL     lower_bnd1(SP), R1    ; current row
0000 190     MOVL     R11, R2              ; current col
0000 191     FETCH    'src_dtype'          ; fetch data from src array
0000 192
0000 193 :+
0000 194 : If the data types of the source and destination arrays is different,
0000 195 : convert the data to the destination type. If scaling is needed (ie if
0000 196 : at least one but not both of the arrays is double) scale the data.
0000 197 :-
0000 198
0000 199     .IF      DIF      src_dtype, dest_dtype    ; src and dest arrays are not
0000 200     : save data type
0000 201     .IF      IDN      src_dtype, G            ; source is gfloat
0000 202     .IF      IDN      dest_dtype, D          ; don't try to CVTGD
0000 203     CVTGH    R0, R0                ; promote source to hfloat
0000 204     .IFF
0000 205     CVT'src_dtype'dest_dtype'        R0, R0    ; dest is not dbl
0000 206     .ENDC
0000 207     .IFF
0000 208     .IF      IDN      src_dtype, D            ; source is double
0000 209     MOVD     R0, -(SP)                ; save the data
0000 210     SF$L    SAVE_FP(FP), R0          ; pass FP to get scale
0000 211     JSB      G*BASS$SCALE_R1         ; get scale in R0 & R1
0000 212     : call a BLISS routine because
0000 213     : the frame offsets are only
```


DECLARATIONS

```
0000 214      : defined for BLISS
0000 215      : scale
0000 216      : can't CVDG
0000 217      : so promote to hfloat
0000 218      : dest is not gfloat
0000 219      : cvt src to dest type
0000 220      :
0000 221      :
0000 222      : convert data from R0 into R0
0000 223      : dest is double
0000 224      : save the data
0000 225      : pass FP to get scale
0000 226      : get scale in R0 & R1
0000 227      : call a BLISS routine because
0000 228      : the frame offsets are only
0000 229      : defined for BLISS
0000 230      : scale
0000 231      : integerize
0000 232      :
0000 233      :
0000 234      :
0000 235      :
0000 236      :
0000 237      :+
0000 238      : Now store the data in the destination array.
0000 239      : Hfloat passed by value takes 4 words, gfloat and double take 2 words, and
0000 240      : all other supported daty types take 1 longword.
0000 241      :-
0000 242      :
0000 243      : dtype is hfloat
0000 244      : pointer to array desc
0000 245      : current row, put in col
0000 246      : current col, put in row
0000 247      :
0000 248      : dtype is gfloat
0000 249      : pointer to array desc
0000 250      : current row, put in col
0000 251      : current col, put in row
0000 252      :
0000 253      : see if dtype is double
0000 254      : pointer to array desc
0000 255      : current row, put in col
0000 256      : current column, put in row
0000 257      : all other data types here
0000 258      : pointer to array desc
0000 259      : current row, put in col
0000 260      : current col, put in row
0000 261      :
0000 262      :
0000 263      : code now same for all dtypes
0000 264      : store value in DATA
0000 265      : store in array
0000 266      : get next column
0000 267      : see if last column done
0000 268      :
0000 269      :
0000 270      : no, continue inner loop
```

DECLARATIONS

```

0000 271 :+
0000 272 : Have completed entire row. See if it was the last row. If not,
0000 273 : continue with next row.
0000 274 :-
0000 275
0000 276 3$: INCL lower_bnd1(SP) ; get next row
0000 277 CMPL lower_bnd1(SP), upper_bnd1(SP) ; see if last row done
0000 278 BGTR 5$
0000 279 BRW LOOP_1ST_SUB'src_dtype'dest_dtype' ; no, continue outer loop
0000 280
0000 281 5$: RET ; yes, finished
0000 282
0000 283 .ENDM

```

BASSMAT_TRN - Transpose one matrix into

```
0000 285 .SBTTL BASSMAT_TRN - Transpose one matrix into another
0000 286 :++
0000 287 FUNCTIONAL DESCRIPTION:
0000 288
0000 289 Transpose one matrix into another. If the src matrix has 2 dimensions,
0000 290 redimension the output matrix to have the number of rows that the src
0000 291 has columns and the number of columns that the src has rows. (thereby
0000 292 ensuring that the dest matrix also has 2 dimensions). Initialize all
0000 293 the necessary looping information on the stack. Conversions will have
0000 294 to be done from the source data type to the destination data type, so
0000 295 divide the looping portion according to the data types.
0000 296
0000 297 CALLING SEQUENCE:
0000 298
0000 299 CALL BASSMAT_TRN (src_matrix.rx.da, dest_matrix.wx.da)
0000 300
0000 301 INPUT PARAMETERS:
0000 302
0000 303 src_matrix = 4
0000 304
0000 305 IMPLICIT INPUTS:
0000 306
0000 307 Scale from the callers frame to scale double precision.
0000 308
0000 309 OUTPUT PARAMETERS:
0000 310
0000 311 dest_matrix = 8
0000 312
0000 313 IMPLICIT OUTPUTS:
0000 314
0000 315 NONE
0000 316
0000 317 FUNCTION VALUE:
0000 318 COMPLETION CODES:
0000 319
0000 320 NONE
0000 321
0000 322 SIDE EFFECTS:
0000 323
0000 324 This routine calls the redimensioning routine and the array element
0000 325 fetch and store routines and therefore may signal any of their errors.
0000 326 It may also signal any of the errors listed in the externals section.
0000 327 It may also cause the destination array to have different dimensions.
0000 328
0000 329 --
0000 330
0000 331 .ENTRY BASSMAT_TRN, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11,IV>
0002 332
0002 333 :+
0002 334 REGISTER USAGE
0002 335 R0 - R8 destroyed by fetch and store routines
0002 336 R9 upper bound for 2nd subscript
0002 337 R10 pointer to array descriptor
0002 338 R11 current value of 2nd subscript
0002 339 :-
0002 340
0002 341 :+
```


BASSMAT_TRN

- Transpose one matrix into

```
0002 342 ; Put routine arguments into registers for ease of use.
0002 343 ; If block 3 of array descriptor (bounds) is not present then error.
0002 344 ; -
0002 345
0002 346 CLRG -(SP)
0004 347 CLRG -(SP)
0006 348 CLRG -(SP)
0008 349 MOVL src_matrix(AP), R10 ; ptr to array descr in R10
000C 350 BBC #DSC$V_FL_BOUNDS, DSC$B_AFLAGS(R10), ERR_ARGDONMAT ; exit if block 3 not
0011 351 ; present in descriptor
0011 352
0011 353
0011 354 ;+
0011 355 ; Set up limits for looping through all elements
0011 356 ; -
0011 357
0011 358 CMPB DSC$B_DIMCT(R10), #2 ; determine # of subscripts
0015 359 BEQLU INIT_SUBS ; 2 subs, initialize loop
0017 360 ; not 2 subs, fall into error
0017 361
0017 362 ERR_MATDIMERR:
0017 363 PUSHL #BASSK_MATDIMERR ; signal error, not 2 dims
001D 364 CALLS #1, G^BASS$STOP ; for src matrix
0024 365
0024 366 ERR_ARGDONMAT:
0024 367 PUSHL #BASSK_ARGDONMAT ; signal error
002A 368 CALLS #1, G^BASS$STOP ; block 2 or 3 absent
0031 369
0031 370 ERR_ILLOPE:
0031 371 PUSHL #BASSK_ILLOPE ; signal error, DSC$A_POINTER
0037 372 CALLS #1, G^BASS$STOP ; same for src & dest matrices
003E 373
003E 374 ;+
003E 375 ; There are 2 subscripts. Make sure the source and dest matrices are not the
003E 376 ; same. Check and redimension the destination array if
003E 377 ; necessary. Put the upper bound for both subscripts on the
003E 378 ; stack and make sure that the lower bound for both subscripts will start
003E 379 ; at 1 (do not alter row or col 0)
003E 380 ; -
003E 381
003E 382 INIT_SUBS:
003E 383 MOVL dest_matrix(AP), R11 ; get pointer to dest matrix
0042 384 CMPB DSC$B_CLASS(R10), #DSC$K_CLASS_A ; is src virtual
0046 385 BNEQU VIRTUAL ; src is virtual go process
0048 386 CMPB DSC$B_CLASS(R11), #DSC$K_CLASS_A ; is dest virtual?
004C 387 BNEQU INIT_SUBS_2 ; yes, cant be same array
004E 388 CMPL DSC$A_POINTER(R10), DSC$A_POINTER(R11) ; are matrices the same?
0053 389 BEQLU ERR_ILLOPE ; yes, error
0055 390 BRB INIT_SUBS_2
0057 391
0057 392 VIRTUAL:
0057 393 CMPB DSC$B_CLASS(R11), #DSC$K_CLASS_A ; is dest virtual
005B 394 BEQLU INIT_SUBS_2 ; no, cant be same array
005D 395 CMPL DSC$E_LOGUNIT(R10), DSC$E_LOGUNIT(R11) ; are matrices same
0062 396 BNEQ INIT_SUBS_2 ; no
0064 397 CMPL DSC$E_BYTEOFF(R10), DSC$E_BYTEOFF(R11) ; are the matrices
0069 398 ; the same, (test for same by
0069 ; same dsc$e_byteoff, dsc$e_logunit
```

```

      C6 13 0069 399 BEQL ERR_ILLOPE ; yes, error
      20 AA DD 0068 400 INIT_SUBS_2:
      28 AA DD 006E 401 PUSHL dsc$1_u1_2(R10) ; 2nd upr bnd, make 1st in dest
      5B DD 0071 402 PUSHL dsc$1_u2_2(R10) ; 1st upr bnd, make 2nd in dest
00000000'GF 03 FB 0073 403 PUSHL R11 ; dest array pointer
      20 AA DD 007A 404 CALLS #3, G*BASSMAT REDIM ; redimension destination
      1C AA DD 007D 405 PUSHL dsc$1_u1_2(R10) ; 1st upper bound
      03 14 0080 406 PUSHL dsc$1_l1_2(R10) ; 1st lower bound
      6E 01 D0 0082 407 BGTR 1$ ; not row 0 or neg, do cols
59 28 AA D0 0085 408 MOVL #1, (SP) ; start with row 1
      24 AA DD 0089 409 1$: MOVL dsc$1_u2_2(R10), R9 ; 2nd upper bound
      03 14 008C 410 PUSHL dsc$1_l2_2(R10) ; 2nd lower bound
      6E 01 D0 008E 411 BGTR SEPARATE_DTYPES ; not col 0 or neg, go loop
      0091 412 MOVL #1, (SP) ; start with col 1
      0091 413
      0091 414 ;+
      0091 415 ; Algorithm now differs according to data types
      0091 416 ;+
      0091 417 ;+
      0091 418 SEPARATE_DTYPES:
05 06 55 5A D0 0091 419 MOVL R10, R5 ; save original pointer
      02 A5 8F 0094 420 5$: CASEB DSC$B_DTYPE(R5), #DSC$K_DTYPE_B, #<DSC$K_DTYPE_D - DSC$K_DTYPE_B>
      0037' 0099 421 2$: .WORD BYTE-2$ ; code for byte dtype
      00B2' 009B 422 .WORD WORD-2$ ; code for word dtype
      1B2D' 009D 423 .WORD LONG-2$ ; code for long dtype
      002A' 009F 424 .WORD ERR_DATTYPERR-2$ ; quad not supported
      28A8' 00A1 425 .WORD FLOAT-2$ ; code for float dtype
      3623' 00A3 426 .WORD DOUBLE-2$ ; code for double dtype
      00A5 427
      00A5 428 ;+
      00A5 429 ; G and H floating fall outside the range of the CASEB, so check for them
      00A5 430 ; separately.
      00A5 431 ;+
      00A5 432 ;+
1B 02 A5 91 00A5 433 CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_G
      03 12 00A9 434 BNEQ 3$
      43D9 31 00AB 435 BRW GFLOAT
      00AE 436
1C 02 A5 91 00AE 437 3$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_H
      03 12 00B2 438 BNEQ 4$
      5163 31 00B4 439 BRW HFLOAT
      00B7 440
1B 02 A5 91 00B7 441 4$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_DSC
      06 12 00BB 442 BNEQ ERR_DATTYPERR
55 04 A5 D0 00BD 443 MOVL 4(R5), R5 ; R5 <-- addr of descriptor
      D1 11 00C1 444 BRB 5$ ; CASE again on dtype in desc
      00C3 445
      00C3 446 ERR_DATTYPERR:
00000000'8F DD 00C3 447 PUSHL #BASS$K_DATTYPERR ; Signal error, unsupported
00000000'GF 01 FB 00C9 448 CALLS #1, G*BASS$$STOP ; dtype in array desc
```

BASSMAT_TRN - Transpose one matrix into

```
00D0 451 ;+
00D0 452 ; Source array is a byte array. Now differentiate on the destination type.
00D0 453 ; -
00D0 454
05 06 55 5B D0 00D0 455 BYTE: MOVL R11, R5 ; move pointer into R5
02 A5 8F 00D3 456 5$: CASEB DSC$B_DTYPE(R5), #DSC$K_DTYPE_B, #<DSC$K_DTYPE_D - DSC$K_DTYPE_B>
020B 00D8 457 1$: .WORD BYTE_TO_BYTE-1$ ; code for byte dtype
03EC 00DC 458 .WORD BYTE_TO_WORD-1$ ; code for word dtype
FFEB 00DE 459 .WORD BYTE_TO_LONG-1$ ; code for long dtype
05CD 00E0 460 .WORD ERR_DATTYPERR-1$ ; quad not supported
07AE 00E2 461 .WORD BYTE_TO_FLOAT-1$ ; code for float dtype
00E4 462 .WORD BYTE_TO_DOUBLE-1$ ; code for double dtype
1B 02 A5 91 00E4 463
03 12 00E8 464 CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_G
0990 31 00EA 465 BNEQ 2$
00ED 466 BRW BYTE_TO_GFLOAT
1C 02 A5 91 00ED 467 2$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_H
03 12 00F1 468 BNEQ 3$
0B6E 31 00F3 469 BRW BYTE_TO_HFLOAT
00F6 470
1B 02 A5 91 00F6 471 3$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_DSC
06 12 00FA 472 BNEQ 4$
55 04 A5 D0 00FC 473 MOVL 4(R5), R5 ; R5 <-- addr of descriptor
D1 11 0100 474 BRB 5$ ; CASE again on dtype in desc
FFBE 31 0102 475
0102 476 4$: BRW ERR_DATTYPERR ; unsupported dtype
0105 477
0105 478
0105 479 ;+
0105 480 ; Now type of source and destination arrays are known. Use the macro to
0105 481 ; generate the code for each case
0105 482 ; -
0105 483
```


BASSMAT_TRN
1-013

H 15

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 12
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

0105 485 BYTE_TO_BYTE: \$BASSMAT_TRN B, B
02E3 486

BASSMAT_TRN
1-013

I 15

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 13
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

02E3 488 BYTE_TO_WORD: SBASSMAT_TRN B, W
04C4 489

BASSMAT_TRN
1-013

J 15

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 14
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

04C4 491 BYTE_TO_LONG: \$BASSMAT_TRN B, L
06A5 492

BASSMAT_TRN
1-013

K 15

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 15
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

06A5 494 BYTE_TO_FLOAT: SBASSMAT_TRN B, F
0886 495

BASSMAT_TRN
1-013

L 15

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 16
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

0886 497 BYTE_TO_DOUBLE: \$BASSMAT_TRN B, D
0A7D 498

BASSMAT_TRN
1-013

M 15

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 17
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

0A7D 500 BYTE_TO_GFLOAT: SBASSMAT_TRN B, G
0C64 501

BASSMAT_TRN
1-013

N 15

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 18
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

OC64 503 BYTE_TO_HFLOAT: \$BASSMAT_TRN B, H
OE4B 504

```
05 06 55 5B D0 0E4B 506 :+
                                0E4B 507 : Source array is a word array. Now differentiate on the destination type.
                                0E4B 508 :-
                                0E4B 509
                                0E4B 510 WORD: MOVL R11, R5 ; move original pointer in R5
                                0E4E 511 5$: CASEB DSC$B_DTYPE(R5), #DSC$K_DTYPE_B, #<DSC$K_DTYPE_D - DSC$K_DTYPE_B>
                                002D 0E53 512 1$: .WORD WORD_TO_BYTE-1$ ; code for byte dtype
                                020E 0E55 513 .WORD WORD_TO_WORD-1$ ; code for word dtype
                                03EC 0E57 514 .WORD WORD_TO_LONG-1$ ; code for long dtype
                                F270 0E59 515 .WORD ERR_DATTYPERR-1$ ; quad not supported
                                05CD 0E5B 516 .WORD WORD_TO_FLOAT-1$ ; code for float dtype
                                07AE 0E5D 517 .WORD WORD_TO_DOUBLE-1$ ; code for double dtype
                                0E5F 518
                                1B 02 A5 91 0E5F 519 CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_G
                                03 12 0E63 520 BNEQ 2$
                                0990 31 0E65 521 BRW WORD_TO_GFLOAT
                                0E68 522
                                1C 02 A5 91 0E68 523 2$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_H
                                03 12 0E6C 524 BNEQ 3$
                                0B6E 31 0E6E 525 BRW WORD_TO_HFLOAT
                                0E71 526
                                1B 02 A5 91 0E71 527 3$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_DSC
                                06 12 0E75 528 BNEQ 4$
                                55 04 A5 D0 0E77 529 MOVL 4(R5), R5 ; R5 <-- addr of descriptor
                                D1 11 0E7B 530 BRB 5$ ; CASE again on dtype in desc
                                F243 31 0E7D 531
                                0E7D 532 4$: BRW ERR_DATTYPERR ; unsupported dtype
                                0E80 533
                                0E80 534 :+
                                0E80 535 : Now type of source and destination arrays are known. Use the macro to
                                0E80 536 : generate the code for each case
                                0E80 537 :-
                                0E80 538
```

BASSMAT_TRN
1-013

C 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 20
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

OE80 540 WORD_TO_BYTE: SBASSMAT_TRN W, B
1061 541

BASSMAT_TRN
1-013

D 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 21
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

1061 543 WORD_TO_WORD: \$BASSMAT_TRN W, W
123F 544

BASSMAT_TRN
1-013

E 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 22
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

123F 546 WORD_TO_LONG: \$BASSMAT_TRN W, L
1420 547

BASSMAT_TRN
1-013

F 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 23
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

1420 549 WORD_TO_FLOAT: \$BASSMAT_TRN W, F
1601 550

BASSMAT_TRN
1-013

G 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 24
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

1601 552 WORD_TO_DOUBLE: SBASSMAT_TRN W, D
17F8 553

BASSMAT_TRN
1-013

H 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 25
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

17F8 555 WORD_TO_GFLOAT: \$BASSMAT_TRN W, G
19DF 556

BASSMAT_TRN
1-013

I 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 26
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

19DF 558 WORD_TO_HFLOAT: \$BASSMAT_TRN W, H
1BC6 559

```

1BC6 561 ;+
1BC6 562 ; Source array is a longword array. Now differentiate on the destination type
1BC6 563 ;+
1BC6 564 ;+
05 06 55 5B DO 1BC6 565 LONG: MOVL R11, R5 ; recover original pointer
02 A5 8F 1BC9 566 5$: CASEB DSC$B_DTYPE(R5), #DSC$K_DTYPE_B, #<DSC$K_DTYPE_D - DSC$K_DTYPE_B>
002D' 1BCE 567 1$: .WORD LONG_TO_BYTE-1$ ; code for byte dtype
020E' 1BD0 568 .WORD LONG_TO_WORD-1$ ; code for word dtype
03EF' 1BD2 569 .WORD LONG_TO_LONG-1$ ; code for long dtype
E4F5' 1BD4 570 .WORD ERR_DATTYPERR-1$ ; quad not supported
05CD' 1BD6 571 .WORD LONG_TO_FLOAT-1$ ; code for float dtype
07AE' 1BD8 572 .WORD LONG_TO_DOUBLE-1$ ; code for double dtype
1B 02 A5 91 1BDA 573
03 12 1BDE 574 CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_G
0990 31 1BE0 575 BNEQ 2$
1BE3 576 BRW LONG_TO_GFLOAT
1C 02 A5 91 1BE3 577 2$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_H
03 12 1BE7 578 BNEQ 3$
0B6E 31 1BE9 579 BRW LONG_TO_HFLOAT
1BEC 580
1B 02 A5 91 1BEC 581 3$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_DSC
06 12 1BF0 582 BNEQ 4$
55 04 A5 DO 1BF2 583 MOVL 4(R5), R5 ; R5 <-- addr of descriptor
D1 11 1BF6 584 BRB 5$ ; CASE again on dtype in desc
E4C8 31 1BF8 585
1BF8 586 4$: BRW ERR_DATTYPERR ; unsupported dtype
1BF8 587
1BF8 588
1BF8 589 ;+
1BF8 590 ; Now type of source and destination arrays are known. Use the macro to
1BF8 591 ; generate the code for each case
1BF8 592 ;+

```

BASSMAT_TRN
1-013

K 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 28
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

1BFB 594 LONG_TO_BYTE: SBASSMAT_TRN L, B
1DDC 595

BASSMAT_TRN
1-013

L 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 29
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

1DDC 597 LONG_TO_WORD: \$BASSMAT_TRN L, W
1FBD 598

BASSMAT_TRN
1-013

M 16

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 30
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (S)

1FBD 600 LONG_TO_LONG: SBASSMAT_TRN L, L
219B 601

BASSMAT_TRN
1-013

B 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 31
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

2198 603 LONG_TO_FLOAT: \$BASSMAT_TRN L, F
237C 604

BASSMAT_TRN
1-013

C 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 32
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

237C 606 LONG_TO_DOUBLE: SBASSMAT_TRN L, D
2573 607

BASSMAT_TRN
1-013

D 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 33
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

2573 609 LONG_TO_GFLOAT: \$BASSMAT_TRN L, G
275A 610

BASSMAT_TRN
1-013

E 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 34
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

275A 612 LONG_TO_HFLOAT: SBASSMAT_TRN L, H
2941 613

BASSMAT_TRN - Transpose one matrix into

```
2941 615 ;+
2941 616 ; Source array is a floating array. Now differentiate on the destination type
2941 617 ; -
2941 618
2941 619 FLOAT: MOVL R11, R5 ; recover original pointer
05 06 55 02 5B D0 2944 620 5$: CASEB DSC$B_DTYPE(R5), #DSC$K_DTYPE_B, #<DSC$K_DTYPE_D - DSC$K_DTYPE_B>
      8F 2949 621 1$: .WORD FLOAT_TO_BYTE-1$ ; code for byte dtype
      002D 294B 622 .WORD FLOAT_TO_WORD-1$ ; code for word dtype
      020E 294D 623 .WORD FLOAT_TO_LONG-1$ ; code for long dtype
      03EF 294F 624 .WORD ERR_DATTYPERR-1$ ; quad not supported
      D77A 2951 625 .WORD FLOAT_TO_FLOAT-1$ ; code for float dtype
      05D0 2953 626 .WORD FLOAT_TO_DOUBL-1$ ; code for double dtype
      07AE 2955 627
1B 02 A5 91 2955 628 CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_G
      03 12 2959 629 BNEQ 2$
      0990 31 295B 630 BRW FLOAT_TO_GFLOA
      295E 631
1C 02 A5 91 295E 632 2$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_H
      03 12 2962 633 BNEQ 3$
      0B6E 31 2964 634 BRW FLOAT_TO_HFLOA
      2967 635
1B 02 A5 91 2967 636 3$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_DSC
      06 12 296B 637 BNEQ 4$
55 04 A5 D0 296D 638 MOVL 4(R5), R5 ; R5 <-- addr of descriptor
      D1 11 2971 639 BRB 5$ ; CASE again on dtype in desc
      2973 640
      D74D 31 2973 641 4$: BRW ERR_DATTYPERR ; unsupported dtype
      2976 642
      2976 643 ;+
      2976 644 ; Now type of source and destination arrays are known. Use the macro to
      2976 645 ; generate the code for each case
      2976 646 ; -
```

BASSMAT_TRN
1-013

G 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 36
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

2976 648 FLOAT_TO_BYTE: SBASSMAT_TRN F, B
2B57 649

BASSMAT_TRN
1-013

H 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 37
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

2B57 651 FLOAT_TO_WORD: SBASSMAT_TRN F, W
2D38 652

BASSMAT_TRN
1-013

I 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 38
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

2D38 654 FLOAT_TO_LONG: SBASSMAT_TRN F, L
2F19 655

BASSMAT_TRN
1-013

J 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 39
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

2F19 657 FLOAT_TO_FLOAT: \$BASSMAT_TRN F, F
30F7 658

BASSMAT_TRN
1-013

K 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 40
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

30F7 660 FLOAT_TO_DOUBL: \$BASSMAT_TRN F, D
32EE 661

BASSMAT_TRN
1-013

L 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 41
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

32EE 663 FLOAT_TO_GFLOA: \$BASSMAT_TRN F, G
34D5 664

BASSMAT_TRN
1-013

M 1

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 42
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

34D5 666 FLOAT_TO_HFLOA: SBASSMAT_TRN F, H
36BC 667

BASSMAT_TRN - Transpose one matrix into

```

36BC 669 :+
36BC 670 : Source array is a double array. Now differentiate on the destination type.
36BC 671 :-
36BC 672
05 06 55 58 DO 36BC 673 DOUBLE: MOVL R11, R5 ; recover original pointer
02 A5 8F 36BC 674 5$: CASEB DSC$B_DTYPE(R5), #DSC$K_DTYPE_B, #<DSC$K_DTYPE_D - DSC$K_DTYPE_B>
002D' 36BC 675 1$: .WORD DOUBLE_TO_BYTE-1$ ; code for byte dtype
021F' 36BC 676 .WORD DOUBLE_TO_WORD-1$ ; code for word dtype
0411' 36BC 677 .WORD DOUBLE_TO_LONG-1$ ; code for long dtype
C9FF' 36BC 678 .WORD ERR_DATTYPERR-1$ ; quad not supported
0603' 36BC 679 .WORD DOUBLE_TO_FLOAT-1$ ; code for float dtype
07F5' 36BC 680 .WORD DOUBLE_TO_DOUBL-1$ ; code for double dtype
36D0 681
18 02 A5 91 36D0 682 CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_G
03 12 36D4 683 BNEQ 2$
09BE 31 36D6 684 BRW DOUBLE_TO_GFLOA
36D9 685
1C 02 A5 91 36D9 686 2$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_H
03 12 36DD 687 BNEQ 3$
0BAD 31 36DF 688 BRW DOUBLE_TO_HFLOA
36E2 689
18 02 A5 91 36E2 690 3$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_DSC
06 12 36E6 691 BNEQ 4$
55 04 A5 DO 36E8 692 MOVL 4(R5), R5 ; R5 <-- addr of descriptor
D1 11 36EC 693 BRB 5$ ; CASE again on dtype in desc
36EE 694
C9D2 31 36EE 695 4$: BRW ERR_DATTYPERR ; unsupported dtype
36F1 696
36F1 697 :+
36F1 698 : Now type of source and destination arrays are known. Use the macro to
36F1 699 : generate the code for each case
36F1 700 :-
```

BASSMAT_TRN
1-013

B 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 44
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

36F1 702 DOUBLE_TO_BYTE: \$BASSMAT_TRN D. B
38E3 703

BASSMAT_TRN
1-013

C 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 45
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

38E3 705 DOUBLE_TO_WORD: \$BASSMAT_TRN D, W
3AD5 706

BASSMAT_TRN
1-013

D 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 46
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

3AD5 708 DOUBLE_TO_LONG: \$BASSMAT_TRN D, L
3CC7 709

BASSMAT_TRN
1-013

E 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 47
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

3CC7 711 DOUBLE_TO_FLOAT: SBASSMAT_TRN D, F
3EB9 712

BASSMAT_TRN
1-013

F 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 48
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

3EB9 714 DOUBLE_TO_DOUBL: \$BASSMAT_TRN D, D
4097 715

BASSMAT_TRN
1-013

G 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 49
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATRN.MAR;1 (5)

4097 717 DOUBLE_TO_GFLOA: \$BASSMAT_TRN D, G
428F 718

BASSMAT_TRN
1-013

H 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 50
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

428F 720 DOUBLE_TO_HFLOA: SBASSMAT_TRN D. H
4487 721

```

4487 723 :+
4487 724 : Source array is a gfloat array. Now differentiate on the destination type.
4487 725 :-
4487 726
05 06 55 5B D0 4487 727 GFLOAT: MOVL R11, R5 ; recover original pointer
06 02 A5 8F 448A 728 5$: CASEB DSC$B_DTYPE(R5), #DSC$K_DTYPE_B, #<DSC$K_DTYPE_D - DSC$K_DTYPE_B>
002D 448F 729 1$: .WORD GFLOAT_TO_BYTE-1$ ; code for byte dtype
0215 4491 730 .WORD GFLOAT_TO_WORD-1$ ; code for word dtype
03FD 4493 731 .WORD GFLOAT_TO_LONG-1$ ; code for long dtype
BC34 4495 732 .WORD ERR_DATTYPERR-1$ ; quad not supported
05E5 4497 733 .WORD GFLOAT_TO_FLOAT-1$ ; code for float dtype
07CD 4499 734 .WORD GFLOAT_TO_DOUBL-1$ ; code for double dtype
449B 735
1B 02 A5 91 449B 736 CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_G
03 12 449F 737 BNEQ 2$
09A0 31 44A1 738 BRW GFLOAT_TO_GFLOA
44A4 739
1C 02 A5 91 44A4 740 2$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_H
03 12 44A8 741 BNEQ 3$
0B80 31 44AA 742 BRW GFLOAT_TO_HFLOA
44AD 743
1B 02 A5 91 44AD 744 3$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_DSC
06 12 44B1 745 BNEQ 4$
55 04 A5 D0 44B3 746 MOVL 4(R5), R5 ; R5 <-- addr of descriptor
D1 11 44B7 747 BRB 5$ ; CASE again on dtype in desc
44B9 748
BC07 31 44B9 749 4$: BRW ERR_DATTYPERR ; unsupported dtype
44BC 750
44BC 751 :+
44BC 752 : Now type of source and destination arrays are known. Use the macro to
44BC 753 : generate the code for each case
44BC 754 :-
44BC 755
```

BASSMAT_TRN
1-013

J 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 52
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

44BC 757 GFLOAT_TO_BYTE: \$BASSMAT_TRN G, B
46A4 758

BASSMAT_TRN
1-013

K 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 53
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

46A4 760 GFLOAT_TO_WORD: SBASSMAT_TRN G, W
488C 761

BASSMAT_TRN
1-013

L 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 54
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

488C 763 GFLOAT_TO_LONG: \$BASSMAT_TRN G, L
4A74 764

BASSMAT_TRN
1-013

M 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 55
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

4A74 766 GFLOAT_TO_FLOAT: \$BASSMAT_TRN G, F
4C5C 767

BASSMAT_TRN
1-013

N 2

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 56
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

4C5C 769 GFLOAT_TO_DOUBL: SBASSMAT_TRN G, D
4E44 770

BASSMAT_TRN
1-013

B 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 57
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

4E44 772 GFLOAT_TO_GFLOA: \$BASSMAT_TRN G, G
502D 773

BASSMAT_TRN
1-013

C 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 58
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

502D 775 GFLOAT_TO_HFLOA: SBASSMAT_TRN G, H
521A 776

```
BASSMAT_TRN - Transpose one matrix into

521A 778 :+
521A 779 : Source array is a hfloat array. Now differentiate on the destination type.
521A 780 :-
521A 781
05 06 55 02 5B D0 521A 782 HFLOAT: MOVL R11, R5 ; recover original pointer
002D 521D 783 5$: CASEB DSC$B_DTYPE(R5), #DSC$K_DTYPE_B, #<DSC$K_DTYPE_D - DSC$K_DTYPE_B>
0215 5222 784 1$: .WORD HFLOAT_TO_BYTE-1$ ; code for byte dtype
03FD 5224 785 .WORD HFLOAT_TO_WORD-1$ ; code for word dtype
AEA1 5226 786 .WORD HFLOAT_TO_LONG-1$ ; code for long dtype
05E5 5228 787 .WORD ERR_DATTYPERR-1$ ; quad not supported
07CD 522A 788 .WORD HFLOAT_TO_FLOAT-1$ ; code for float dtype
522C 789 .WORD HFLOAT_TO_DOUBL-1$ ; code for double dtype
522E 790
1B 02 A5 91 522E 791 CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_G
03 12 5232 792 BNEQ 2$
09B6 31 5234 793 BRW HFLOAT_TO_GFLOA
5237 794
1C 02 A5 91 5237 795 2$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_H
03 12 523B 796 BNEQ 3$
0B9A 31 523D 797 BRW HFLOAT_TO_HFLOA
5240 798
1B 02 A5 91 5240 799 3$: CMPB DSC$B_DTYPE(R5), #DSC$K_DTYPE_DSC
06 12 5244 800 BNEQ 4$
55 04 A5 D0 5246 801 MOVL 4(R5), R5 ; R5 <-- addr of descriptor
D1 11 524A 802 BRB 5$ ; CASE again on dtype in desc
524C 803
AE74 31 524C 804 4$: BRW ERR_DATTYPERR ; unsupported dtype
524F 805
524F 806 :+
524F 807 : Now type of source and destination arrays are known. Use the macro to
524F 808 : generate the code for each case
524F 809 :-
524F 810
```

BASSMAT_TRN
1-013

E 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 60
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

524F 812 HFLOAT_TO_BYTE: \$BASSMAT_TRN H. B
5437 813

BASSMAT_TRN
1-013

F 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 61
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

5437 815 HFLOAT_TO_WORD: \$BASSMAT_TRN H, W
561F 816

BASSMAT_TRN
1-013

G 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 62
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

561F 818 HFLOAT_TO_LONG: SBASSMAT_TRN H, L
5807 819

BASSMAT_TRN
1-013

H 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 63
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

5807 821 MFLOAT_TO_FLOAT: \$BASSMAT_TRN H, F
59EF 822

BASSMAT_TRN
1-013

1 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 64
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

59EF 824 HFLOAT_TO_DOUBL: \$BASSMAT_TRN H, D
5BED 825

BASSMAT_TRN
1-013

J 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 65
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

SBED 827 HFLOAT_TO_GFLOA: \$BASSMAT_TRN H, G
SDDA 828

BASSMAT_TRN
1-013

K 3

BASSMAT_TRN - Transpose one matrix into 15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 66
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

SDDA 830 HFLOAT_TO_HFLOA: \$BASSMAT_TRN H, H
SFC3 831
SFC3 832 .END

; end of BASSMAT_TRN

BASSMAT TRN
Symbol Table

L 3

15-SEP-1984 23:55:09 VAX/VMS Macro V04-00 Page 67
6-SEP-1984 10:31:25 [BASRTL.SRC]BASMATTRN.MAR;1 (5)

BASSSCALE_R1	*****	X	00	DSCSL_L1_1	= 00000018		
BASSSTOP	*****	X	00	DSCSL_L1_2	= 0000001C		
BASSFETCH_BFA	*****	X	00	DSCSL_L2_2	= 00000024		
BASSFET_FA_B_R8	*****	X	00	DSCSL_LOGUNIT	= FFFFFFFC		
BASSFET_FA_D_R8	*****	X	00	DSCSL_M1	= 00000014		
BASSFET_FA_F_R8	*****	X	00	DSCSL_M2	= 00000018		
BASSFET_FA_G_R8	*****	X	00	DSCSL_U1_1	= 0000001C		
BASSFET_FA_H_R8	*****	X	00	DSCSL_U1_2	= 00000020		
BASSFET_FA_L_R8	*****	X	00	DSCSL_U2_2	= 00000028		
BASSFET_FA_W_R8	*****	X	00	DSCSV_FL_BOUNDS	= 00000007		
BASSK_ARGDONMAT	*****	X	00	DSCSW_LENGTH	= 00000000		
BASSK_DATTYPERR	*****	X	00	DTYPE	= 0000000E		
BASSK_ILLOPE	*****	X	00	ERR_ARGDONMAT	00000024	R	02
BASSK_MATDIMERR	*****	X	00	ERR_DATTYPERR	000000C3	R	02
BASSMAT_REDIM	*****	X	00	ERR_ILLOPE	00000031	R	02
BASSMAT_TRN	00000000	RG	02	ERR_MATDIMERR	00000017	R	02
BASSSTORE_BFA	*****	X	00	FLOAT	00002941	R	02
BASSSTO_FA_B_R8	*****	X	00	FLOAT_TO_BYTE	00002976	R	02
BASSSTO_FA_D_R8	*****	X	00	FLOAT_TO_DOUBL	000030F7	R	02
BASSSTO_FA_F_R8	*****	X	00	FLOAT_TO_FLOAT	00002F19	R	02
BASSSTO_FA_G_R8	*****	X	00	FLOAT_TO_GFLOA	000032EE	R	02
BASSSTO_FA_H_R8	*****	X	00	FLOAT_TO_HFLOA	000034D5	R	02
BASSSTO_FA_L_R8	*****	X	00	FLOAT_TO_LONG	00002D38	R	02
BASSSTO_FA_W_R8	*****	X	00	FLOAT_TO_WORD	00002B57	R	02
BYTE	000000D0	R	02	GFLOAT	00004487	R	02
BYTE_TO_BYTE	00000105	R	02	GFLOAT_TO_BYTE	000044BC	R	02
BYTE_TO_DOUBLE	00000886	R	02	GFLOAT_TO_DOUBL	00004C5C	R	02
BYTE_TO_FLOAT	000006A5	R	02	GFLOAT_TO_FLOAT	00004A74	R	02
BYTE_TO_GFLOAT	00000A7D	R	02	GFLOAT_TO_GFLOA	00004E44	R	02
BYTE_TO_HFLOA	00000C64	R	02	GFLOAT_TO_HFLOA	0000502D	R	02
BYTE_TO_LONG	000004C4	R	02	GFLOAT_TO_LONG	0000488C	R	02
BYTE_TO_WORD	000002E3	R	02	GFLOAT_TO_WORD	000046A4	R	02
CLASS	= 0000000F			HFLOAT	0000521A	R	02
DATA	= 00000014			HFLOAT_TO_BYTE	0000524F	R	02
DEST_MATRIX	= 00000008			HFLOAT_TO_DOUBL	000059EF	R	02
DOUBLE	000036BC	R	02	HFLOAT_TO_FLOAT	00005807	R	02
DOUBLE_TO_BYTE	000036F1	R	02	HFLOAT_TO_GFLOA	00005BED	R	02
DOUBLE_TO_DOUBL	00003EB9	R	02	HFLOAT_TO_HFLOA	00005DDA	R	02
DOUBLE_TO_FLOAT	00003CC7	R	02	HFLOAT_TO_LONG	0000561F	R	02
DOUBLE_TO_GFLOA	00004097	R	02	HFLOAT_TO_WORD	00005437	R	02
DOUBLE_TO_HFLOA	0000428F	R	02	INIT_S0BS	0000003E	R	02
DOUBLE_TO_LONG	00003AD5	R	02	INIT_SUBS_2	0000006B	R	02
DOUBLE_TO_WORD	000038E3	R	02	LONG	00001BC6	R	02
DSCSA_X0	= 00000010			LONG_TO_BYTE	00001BFB	R	02
DSCSA_POINTER	= 00000004			LONG_TO_DOUBLE	0000237C	R	02
DSCSB_AFLAGS	= 0000000A			LONG_TO_FLOAT	0000219B	R	02
DSCSB_CLASS	= 00000003			LONG_TO_GFLOA	00002573	R	02
DSCSB_DIMCT	= 0000000B			LONG_TO_HFLOA	0000275A	R	02
DSCSB_DTYPE	= 00000002			LONG_TO_LONG	00001FBD	R	02
DSCBK_CLASS_A	= 00000004			LONG_TO_WORD	00001DDC	R	02
DSCBK_CLASS_BFA	= 000000BF			LOOP_1ST_SUBBB	00000105	R	02
DSCBK_DTYPE_B	= 00000006			LOOP_1ST_SUBBD	00000886	R	02
DSCBK_DTYPE_D	= 0000000B			LOOP_1ST_SUBBF	000006A5	R	02
DSCBK_DTYPE_DSC	= 00000018			LOOP_1ST_SUBBG	00000A7D	R	02
DSCBK_DTYPE_G	= 0000001B			LOOP_1ST_SUBBH	00000C64	R	02
DSCBK_DTYPE_H	= 0000001C			LOOP_1ST_SUBBL	000004C4	R	02
DSCBL_BYTEOFF	= FFFFFFFB			LOOP_1ST_SUBBW	000002E3	R	02

LOOP_1ST_SUBDB	000036F1	R	02
LOOP_1ST_SUBDD	00003EB9	R	02
LOOP_1ST_SUBDF	00003CC7	R	02
LOOP_1ST_SUBDG	00004097	R	02
LOOP_1ST_SUBDH	0000428F	R	02
LOOP_1ST_SUBDL	00003AD5	R	02
LOOP_1ST_SUBDW	000038E3	R	02
LOOP_1ST_SUBFB	00002976	R	02
LOOP_1ST_SUBFD	000030F7	R	02
LOOP_1ST_SUBFF	00002F19	R	02
LOOP_1ST_SUBFG	000032EE	R	02
LOOP_1ST_SUBFH	000034D5	R	02
LOOP_1ST_SUBFL	00002D38	R	02
LOOP_1ST_SUBFW	00002B57	R	02
LOOP_1ST_SUBGB	000044BC	R	02
LOOP_1ST_SUBGD	00004C5C	R	02
LOOP_1ST_SUBGF	00004A74	R	02
LOOP_1ST_SUBGG	00004E44	R	02
LOOP_1ST_SUBGH	0000502D	R	02
LOOP_1ST_SUBGL	0000488C	R	02
LOOP_1ST_SUBGW	000046A4	R	02
LOOP_1ST_SUBHB	0000524F	R	02
LOOP_1ST_SUBHD	000059EF	R	02
LOOP_1ST_SUBHF	00005807	R	02
LOOP_1ST_SUBHG	00005BED	R	02
LOOP_1ST_SUBHH	00005DDA	R	02
LOOP_1ST_SUBHL	0000561F	R	02
LOOP_1ST_SUBHW	00005437	R	02
LOOP_1ST_SUBLB	00001BFB	R	02
LOOP_1ST_SUBLD	0000237C	R	02
LOOP_1ST_SUBLF	0000219B	R	02
LOOP_1ST_SUBLG	00002573	R	02
LOOP_1ST_SUBLH	0000275A	R	02
LOOP_1ST_SUBLL	00001FBD	R	02
LOOP_1ST_SUBLW	00001DDC	R	02
LOOP_1ST_SUBWB	00000E80	R	02
LOOP_1ST_SUBWD	00001601	R	02
LOOP_1ST_SUBWF	00001420	R	02
LOOP_1ST_SUBWG	000017F8	R	02
LOOP_1ST_SUBWH	000019DF	R	02
LOOP_1ST_SUBWL	0000123F	R	02
LOOP_1ST_SUBWW	00001061	R	02
LOOP_2ND_SUBBB	00000108	R	02
LOOP_2ND_SUBBD	00000889	R	02
LOOP_2ND_SUBBF	000006A8	R	02
LOOP_2ND_SUBBG	00000A80	R	02
LOOP_2ND_SUBBH	00000C67	R	02
LOOP_2ND_SUBBL	000004C7	R	02
LOOP_2ND_SUBBW	000002E6	R	02
LOOP_2ND_SUBDB	000036F4	R	02
LOOP_2ND_SUBDD	00003EBC	R	02
LOOP_2ND_SUBDF	00003CCA	R	02
LOOP_2ND_SUBDG	0000409A	R	02
LOOP_2ND_SUBDH	00004292	R	02
LOOP_2ND_SUBDL	00003AD8	R	02
LOOP_2ND_SUBDW	000038E6	R	02
LOOP_2ND_SUBFB	00002979	R	02

LOOP_2ND_SUBFD	000030FA	R	02
LOOP_2ND_SUBFF	00002F1C	R	02
LOOP_2ND_SUBFG	000032F1	R	02
LOOP_2ND_SUBFH	000034D8	R	02
LOOP_2ND_SUBFL	00002D3B	R	02
LOOP_2ND_SUBFW	00002B5A	R	02
LOOP_2ND_SUBGB	000044BF	R	02
LOOP_2ND_SUBGD	00004C5F	R	02
LOOP_2ND_SUBGF	00004A77	R	02
LOOP_2ND_SUBGG	00004E47	R	02
LOOP_2ND_SUBGH	00005030	R	02
LOOP_2ND_SUBGL	0000488F	R	02
LOOP_2ND_SUBGW	000046A7	R	02
LOOP_2ND_SUBHB	00005252	R	02
LOOP_2ND_SUBHD	000059F2	R	02
LOOP_2ND_SUBHF	0000580A	R	02
LOOP_2ND_SUBHG	00005BF0	R	02
LOOP_2ND_SUBHH	00005DDD	R	02
LOOP_2ND_SUBHL	00005622	R	02
LOOP_2ND_SUBHW	0000543A	R	02
LOOP_2ND_SUBLB	00001BFE	R	02
LOOP_2ND_SUBLD	0000237F	R	02
LOOP_2ND_SUBLF	0000219E	R	02
LOOP_2ND_SUBLG	00002576	R	02
LOOP_2ND_SUBLH	0000275D	R	02
LOOP_2ND_SUBLL	00001FC0	R	02
LOOP_2ND_SUBLW	00001DDF	R	02
LOOP_2ND_SUBWB	00000E83	R	02
LOOP_2ND_SUBWD	00001604	R	02
LOOP_2ND_SUBWF	00001423	R	02
LOOP_2ND_SUBWG	000017FB	R	02
LOOP_2ND_SUBWH	000019E2	R	02
LOOP_2ND_SUBWL	00001242	R	02
LOOP_2ND_SUBWW	00001064	R	02
LOWER_BND1	= 00000004		
LOWER_BND2	= 00000000		
MTH\$DINT_R4	*****	X	00
POINTER	= 00000010		
SEPARATE_DTYPES	00000091	R	02
SF\$L_SAVE_FP	= 0000000C		
SRC_MATRIX	= 00000004		
STR_LEN	= 0000000C		
UPPER_BND1	= 00000008		
VALUE_DESC	= 0000000C		
VIRTUAL	00000057	R	02
WORD	00000E4B	R	02
WORD_TO_BYTE	00000E80	R	02
WORD_TO_DOUBLE	00001601	R	02
WORD_TO_FLOAT	00001420	R	02
WORD_TO_GFLOAT	000017FB	R	02
WORD_TO_HFLOAT	000019DF	R	02
WORD_TO_LONG	0000123F	R	02
WORD_TO_WORD	00001061	R	02

! Psect synopsis !

PSECT name	Allocation	PSECT No.	Attributes
ABS	00000000 (0.)	00 (0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
\$ABSS	00000000 (0.)	01 (1.)	NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE
_BAS\$CODE	00005FC3 (24515.)	02 (2.)	PIC USR CON REL LCL SHR EXE RD NOWRT NOVEC LONG

! Performance indicators !

Phase	Page faults	CPU Time	Elapsed Time
Initialization	28	00:00:00.08	00:00:00.31
Command processing	102	00:00:00.66	00:00:02.89
Pass 1	1020	00:00:40.75	00:01:26.26
Symbol table sort	6	00:00:01.85	00:00:09.19
Pass 2	635	00:00:09.69	00:00:32.14
Symbol table output	89	00:00:00.22	00:00:02.31
Psect synopsis output	7	00:00:00.04	00:00:00.21
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	1890	00:00:53.31	00:02:13.34

The working set limit was 750 pages.
297708 bytes (582 pages) of virtual memory were used to buffer the intermediate code.
There were 60 pages of symbol table space allocated to hold 369 non-local and 824 local symbols.
832 source lines were read in Pass 1, producing 75 object records in Pass 2.
32 pages of virtual memory were used to define 11 macros.

! Macro library statistics !

Macro library name	Macros defined
\$255\$DUA28:[BASRTL.OBJ]BASRTL.MLB;1	2
\$255\$DUA28:[SYSLIB]STARLET.MLB;2	5
TOTALS (all libraries)	7

493 GETS were required to define 7 macros.

There were no errors, warnings or information messages.

MACRO/ENABLE=SUPPRESSION/DISABLE=(GLOBAL,TRACEBACK)/LIS=LIS\$:BASMATTRN/OBJ=OBJ\$:BASMATTRN MSRC\$:BASMATTRN/UPDATE=(ENH\$:BASMATTRN)+L I

0027 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

BASMATSUB
LIS

BASMATSCA
LIS

BASMATRN
LIS

0028 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

BASMD
LIS

BASMDL
LIS

BASNOTIMP
LIS

BASMOVEAR
LIS

BASMSGDEF
LIS

BASMSGGEN
LIS

BASONECHR
LIS

BASMOVE
LIS

BASNUM
LIS

BASNAMEAS
LIS

BASNUM
LIS